

KP1401

desk reader

As the first megapixel scanner on the market, the **KP1401 desk reader** II reads 1D and 2D barcodes, including Aztec, with speed and ease from paper and from a mobile phone screen. With user friendliness being at the forefront of POS systems, the **KP1401 desk reader** features soft illumination with a 10-degree tilt that insures comfort for both employees and customers. Combined with its superior performance and level of comfort, the **KP1401 desk reader** is the perfect addition to any POS system.



2D



1D



1M PIXEL
SENSOR



1.5M DROP



IP 50



USB

KP1401 *desk reader*

Main Characteristics

Physical	Dimensions	Height 93 mm, Width 95mm, Depth 157 mm	
	Weight	298 gr, without cable	
	Cable	Removable Straight 2.0 m	
	Connector Type	RJ-45 phone jack connector	
	Case Material	PC	
	Indicator	Beeper, LED	
Communication	Interface Supported	USB Keyboard, USB virtual COM RS-232, (optional)	
Performance	Operating Mode	Hand-held, Auto-detection	
	Programming Method	Manual (reading special barcode)	
	Firmware Upgrade	Supported	
	Input Voltage	USB 5 \pm 0.25VDC	
	Current	Standby: 110 mA Scanning: 370 mA	
	Image Size	1280 x 800pixels	
	Imager Field of View	Horizontal: 64°, vertical: 44°	
	Scanning Angle	\pm 70°, \pm 70°, 360° (skew, pitch, roll)	
	Print Contrast	20% minimum reflective difference	
	Minimum Resolution	SR: 1D (Code 128) : 4mil	
	Decoding Depth	5 mil Code39 (3 chars) 5mm – 55mm 10 mil Code39 (3 chars) 0mm – 140mm 13 mil UPC (6 chars) 0 mm – 150mm 20 mil Code39 (1 char) 0mm – 239mm 6.7 mil PDF417 (20 chars) 15mm – 60mm 10 mil QR (20 chars) 0mm – 40mm 20 mil QR (20 chars) 0mm – 150mm	
Data Capture	Decoding Capability 1D	UPC-A, UPC-E, UPC-EI, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5(Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/Plessey, UK/Plessey, China Post, China Finance, Telepen, GSI DataBar (formerly RSS) variants	
	Decoding Capability 2D	PDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, MicroQR Code, MicroPDF417	
Environmental	Temperature	Operating -20° to 55°C Storage -20° to 75°C	
	Humidity	5% to 95% (non-condensing)	
	Sailing	IP50	
	Safety	Safety: EN62471:2008 - EN60950 EMC: EN55022 - EN55024 Drop: 30+ times of 1.5m to concrete	



RETAIL



HEALTHCARE



TICKETING

The information in this document is subject to change without notice and should not be construed as a commitment by Kaptur. All reasonable precautions have been taken, Kaptur assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.

Europe Office
Via dei Boschi, 2/13
33040 Pradamano (UD) ITALY
info@kaptur-id.com
www.kaptur-id.com

Hong Kong Office
407, 4th floor, Sunrise Industry Building,
10 Hong Man Street, Chai Wan, HK SAR
info@kaptur-id.com
www.kaptur-id.com

KP1401_EN_V1.01

kaptur

PRECISE DATA DEVICES